

1K FAST FILLER

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

FAST FILLER IS PIGMENTED NITROCELLULOSE FILLER BLENDED WITH MODIFIED ALKYD RESINS AND SELECTED FILLERS. IT IS FORMULATED TO GIVE A HIGH COVERING PROPERTY, GOOD SANDING ABILITY AND GOOD ELASTICITY.

DRYING TIME

SURFACE DRY	15 MIN
COMPLETE DRY	40 :60 MIN



1K FAST FILLER

USES

FAST FILLER CAN BE USED FOR ALL TYPE OF WOODEN FURNITURE, CHAIRS, TURNED PIECES, CLOTHES-HOOKS, PICTURE MOLDING AND RELATED PRODUCTS.

CHARACTERISTICS AND PHYSICAL PROPERTIES

APPEARANCE	DARK
SOLID BY WEIGHT %	60 ± 0.5
SPECIFIC GRAVITY (KG / L)	1.32 ± 0.02
VISCOSITY (CENTIPOISE)	18.000 ± CP

METHOD OF APPLICATION

BY SPRAYING (3- 4 ATM) / BRUSHING ..

- FOR ALL WOODS; 1 – 2 COATS THINNED AT 30% THINNER..
- SAND THE SURFACE WELL WITH MANUAL SANDING OR AUTOMATIC SANDING MACHINE..
- ENSURE THAT THE SURFACE IS CLEAN AND WELL PREPARED PRIOR TO FINAL COATING..

STORAGE

KEEP MATERIAL IN A COOL PLACE BELOW 25°C. KEEP THE CONTAINER TIGHTLY CLOSED.
SHELF LIFE OF 2 YEARS.

CLEANING OF TOOLS

ALL TOOLS SHOULD BE CLEANED WITH WASH THINNER.

PACKING

AVAILABLE IN 1 KG , 4 KG.

PHYSIOLOGICAL HAZARDS

FAST FILLER DOES NOT CONTAIN DANGEROUS SOLVENTS, NEVERTHELESS, GOOD VENTILATION IN WORKING ROOMS IS RECOMMENDED AS WELL AS THE USE OF SAFETY TOOLS AND EQUIPMENT. FAST FILLER IS FLAMMABLE AND HARMFUL IF SWALLOWED. IF CONTACT WITH EYES OR SKIN OCCURS, WASH WELL WITH FRESH WATER AND SEEK IMMEDIATE MEDICAL ADVICE.