

Light Wight polyester putty

Technical Data Sheet

Description

Two- component creamy polyester putty a low density which give you maximum filling with minimum amount, it is easy to spread with no- sagging even on vertical surfaces, rabidly cured with no- shrinkage and easy to sand with excellent adhesion to all substrates. Vacuum processed to reduce pinholes and tack free finish helps avoid clogging in sand paper.



Technical data

Composition : Unsaturated polyester resin and special additives.
 Color : White- gray- yellow
 Specific weight : 0.05 ± 1.2
 Safety data : See safety data sheet

Surface preparation



-Iron, steel plate



-Clean well the surface to be treated with (Mido cleanser)
 Make sure it is dry and free from silicone , wax and grease .
 - On aged topcoat, sand and clean the surface before applying.

Cautions

Mix well the filler with %3-2 paste hardener
 Do not exceed with the hardener to avoid risk of staining during painting operation
 Do not utilized the product at temperatures below 5°C
 Store in a cool and dry place.

Processing



3-2 % peroxide paste hardener
 pot life 5-3' at 25°C



> 30' at 20°C



P60 - P120 roughing –out
 P180 - P220 finishing



Application with putty knife
 plastic or rubber spreader



7-5' at 1 m

The information this data sheet is given to the best of our knowledge based on laboratory testing and Practical experience. However, as the product is often used under conditions beyond our control we can't guarantee anything but the quality of the product itself.

Light Wight polyester putty

Technical Data Sheet

Tools cleaning

With Nitro thinner

Shelf life

Minimum 1 year if The product stored in dry space provided with adequate Ventilation at 25c & %65 R.H.

The information this data sheet is given to the best of our knowledge based on laboratory testing and Practical experience. However, as the product is often used under conditions beyond our control we can't guarantee anything but the quality of the product itself.