

Perfect Isolater Under Coat

Technical Data Sheet

Description

One pack undercoat for cars. Thanks to its special pigment and binding agent composition it offers excellent anticorrosion properties and covers effectively and sound deadens.



Technical data

Composition: Alkyd resin and special additives.

Color: Black- Gray- White.

Specific weight: 1.4- 1.6 gm/cm³ Safety data: See safety data sheet

Surface preparation



-Iron, steel plate



- -Clean well the surface to be treated with (Mido cleanser) Make sure it is dry and free from silicone , wax and grease .
- On aged topcoat, sand and clean the surface before applying the filler. .

Cautions

It is recommended that the steel temperature should be min .3oc above the dew point of the Air in the vicinity of the steel.

Store in a cool and dry place

Processing

Add about 10 % up to 30 % suitable thinner or(till the required viscosity) then use . Apply using special spray gun.

Tools cleaning

With Nitro thinner

The information this data sheet is given to the best of our knowledge based on laboratory testing and Practical experience. However, as the product is often used under conditions beyond our control we can't guarantee anything but the quality of the product itself.



Perfect Isolater Under Coat

Technical Data Sheet

Shelf life

Minimum 2 year if The product stored in dry space provided with adequate Ventilation at 25° c & 65 % R.H.

The information this data sheet is given to the best of our knowledge based on laboratory testing and Practical experience. However, as the product is often used under conditions beyond our control we can't guarantee anything but the quality of the product itself.